

Available in 4 colours

Onduline Classic® sheets are the outcome of a unique technology known as 'pre-pigmentation', which enables a bitumen-based composite to be coloured full-depth.



Black



Brown



Red



Green

Accessories

ROOF RIDGE

Length	90 cm
Width	2x 20 cm
Thickness	3 mm



TACKS

With their broad ultra-strong plastic heads, the Onduline Classic® tacks deliver optimum seal integrity to Onduline Classic® roofings.



ONDULINE CLASSIC®

Technical specifications

Length of a sheet	200 cm
Width of a sheet	95 cm
Thickness of a sheet	3 mm
Height of a corrugation	38 mm
Weight of a sheet	6,40 kg



Certifications

Onduline Classic® complies with the following standards:
EN 534

ISO 9001: 2000 - ISO 14001

CSTB: AT/04/1779 - AT 5/03 1690 - AT 5/99 1424

CSTC/UBat: ATG 01/1938

BBA: C 87/1832 C

ITB: 500 / 02 AT 1 2145 / 2002

Onduline

Onduline SA
35 rue Baudin, 32300 Lavaur (France)
T : + 33 1 55 63 80 30
info@onduline.com - www.onduline.com

ONDULINE CLASSIC®



Universal cladding sheets

Simplicity
Reliability
Commitment



Onduline®

www.onduline.com

Simplicity

Onduline Classic sheets have been installed on the roofs of residential, industrial and agricultural buildings on more than 100 countries.*



A UNIVERSAL TYPE OF ROOFING

Thanks to their reduced weight (about 3 kg/m²) and their great mechanical flexibility, **Onduline Classic*** sheets can be installed on an extremely diverse range of lightweight roof structures.



PRACTICAL TO INSTALL

Onduline Classic* sheets only require a very simple toolkit to install: a hammer for securing the sheets and a band saw for cutting them down to size.



AN ALL-TERRAIN MATERIAL

In contrast to many roofing materials which are unable to withstand journeys on rough roads, **Onduline Classic*** sheets never break while in transit.



Reliability

Onduline Classic sheets were launched in 1950 by the Onduline Group and the R&D department at Onduline has worked ceaselessly to further improve the product.*



GUARANTEED SEAL INTEGRITY

Incorporating the properties of the finest grades of bitumen, **Onduline Classic*** sheets deliver perfect seal integrity in all climates.



OPTIMUM INSULATION

Thermally speaking, **Onduline Classic*** composite has one of the lowest heat conducting coefficients on the market. Not only that, it also insulates well against the noise of heavy rainfall and is able to withstand Siberian levels of sub-zero weather.

PERFECT VENTILATION

The corrugated shape of **Onduline Classic*** sheets makes roof structures easier to ventilate and delivers great temperature resistance to any roof.



Commitment

*The plants where **Onduline Classic*** is manufactured are equipped with treatment systems for gas effluents, and do not jettison liquid waste in any form.*



THE FRUITS OF GREEN TECHNOLOGY

Onduline Classic* sheets are manufactured from recycled fibre, in which field the Onduline Group is an established player (recycling 200,000 tons per annum).



A SAFE PRODUCT

It almost goes without saying that **Onduline Classic*** sheets contain no asbestos. Rainwater collected from an **Onduline Classic*** sheet is suitable for all cultivation purposes.



IDEAL PROPERTIES FOR HURRICANE AREAS

Lightweight, non-cutting and ultra-flexible, **Onduline Classic*** sheets are specified by a great many architects in regions of the world exposed to the risk of hurricanes.

