

## DECLARATION OF PERFORMANCE Under the CPR EU 305/2011 DoP N° 22 SA03 Bardoline Classic

1. Unique identification code of the product-type:

**Bardoline Classic Rectangular SA03 - Bardoline Classic Beaver SA03 – Bardoline Classic Triangular SA03.**

2. Intended use or uses of the construction product, in accordance with the applicable harmonized technical specification, as foreseen by the manufacturer:

**For roof and external wall covering**

3. Name, registered trade name or registered trade mark and contact address of the manufacturer as required under Article 11(5):

**Onduline**  
**24, quai Galliéni**  
**F- 92 150 Suresnes – France**  
**Tel : +33 1 55 63 80 10 Fax : +33 1 41 34 30 54**  
[www.onduline.com](http://www.onduline.com)

4. Where applicable, name and contact address of the authorized representative whose mandate covers the tasks specified in Article 12(2):

**Not Applicable**

5. System or systems of assessment and verification of constancy of performance of the construction product as set out in CPR, Annex V:

**System 4**

6.a In case of the declaration of performance concerning a construction product covered by a harmonized standard:

**Not Applicable**

Notified body: **0970 - ITC-CNR ISTITUTO PER LE TECNOLOGIE DELLA COSTRUZIONE** - Viale Lombardia, 49 - 20098 - San Giuliano Milanese (MI) - Country : Italy

6.b European Assessment Document : **220020-00-0402**

European Technical Assessment : **ETA 18/1036**

### 7. Declared performances

Essential characteristics	Performance	Technical specification
<b>Mechanical resistance</b>		ETA 18/1036
<b>Tensile strength(width)</b>	> 600 N/50 mm	
<b>Tensile strength(height)</b>	> 400 N/50 mm	
<b>Nails shank tear resistance</b>	> 100 N	
<b>Reaction to fire</b>	E	
<b>External fire performance</b>	Brooft4	
<b>Water permeability</b>	Bitumen ≥1000g/m²	
<b>Dimensional variation</b>	MDV±3 mm	
<b>Durability of mechanical resistance</b>	pass	
<b>Durability of water permeability:</b>		
- Flow resistance at elevated temperature	<1 mm	
- Adhesion of the protective finishing	<1.5 g	
- Water absorption	<1%	
<b>Resistance to fixing</b>	>100 N	
<b>Dangerous substances</b>	NPD – see notes 1 & 2	

Note 1 ; This product does not contain asbestos or tar constituents


Note 2 : in the absence of European harmonized test method verification and declaration on content/release has to be done taking account national provisions in the place of use.

8. Appropriate Technical Documentation and/or Specific Technical documentation : **NO**

The performance of the product identified above is in conformity with the set of declared performances. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

**Christophe Rohart**  
R&D Director



Suresnes, 15/04/2019 rev.1