

DECLARATION OF PERFORMANCE
Under the CPR EU 305/2011
DOP 2020-001 SA16

1. Unique identification code of the product-type: **ONDUCLAIR® PVC 95|35-07 (Clear - Bronze) - ONDUCLAIR® PVC 95|35-08 (Clear - Bronze) - ONDUCLAIR® PVC Greca 70|18-07 (Clear - Bronze).**

2. Intended use or uses of the construction product, in accordance with the applicable harmonized technical specification, as foreseen by the manufacturer:

Light transmitting extruded single skin profiled plastics sheets for internal and external roofs, wall and ceilings.

3. Name, registered trade name or registered trade mark and contact address of the manufacturer as required under Article 11(5):

Onduline
24, quai Galliéni
F- 92 150 Suresnes – France
Tel : +33 1 55 63 80 10 Fax : +33 1 41 34 30 54
www.onduline.com

4. Where applicable, name and contact address of the authorized representative whose mandate covers the tasks specified in Article 12(2): **Not relevant**

5. System or systems of assessment and verification of constancy of performance of the construction product as set out in CPR, Annex V: **System 3 – NB 2137 (CREPIM FRANCE)**

6.a. In case of the declaration of performance concerning a construction product covered by a harmonized standard:

EN 1013:2012 + A1 2014

6.b. European Assessment document : **NOT Applicable**

European Technical document : **NOT Applicable**

7. Declared performances

Essential characteristics	Performance	Harmonized Technical Specification	Harmonized Standard
External fire performance	F_{roof} (NPD)	5.14	EN 1013:2012 + A1 2014
Reaction to fire (Clear 08) / (Clear 07- Bronze 07 & 08)	(B-s2,d0) / (B-s3,d0)	5.13	
Water vapour permeability	0.8 x 10⁻⁵ mg/(m.h. Pa)	5.10	
Water / air permeability	Pass	5.11	
Release of dangerous substances	NPD	5.20	
Dimensional tolerances	Pass	5.2	
<i>Shatter properties (safe breakability) as:</i>			
Small hard body impact resistance	Pass	5.8	EN 1013:2012 + A1 2014
Soft body impact resistance	NPD	5.8	
Resistance to fixings	Method of fixing; advised separately.	5.19	
<i>Durability as variation (after aging) of :</i>			
- Yellow index (Clear) / (Bronze)	(Class A1) / (Class A2)	5.5.3	EN 1013:2012 + A1 2014
- Light transmission	NPD	5.5.4	
- Bending resistance	NPD	5.5.5	
- Elasticity Modulus (flexion)	NPD	5.5.5	

8. Appropriate Technical Documentation and/or Specific Technical documentation: **NO**

The performance of the product identified in points 1 & 2 is in conformity with the set of declared performances in point 7 . This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified in point 3.

Signed for and on behalf of the manufacturer by:

Christophe ROHART
R&D Director

Suresnes, 24/08/2020 rev.1

