

## DECLARATION OF PERFORMANCE Under the CPR EU 305/2011 No. 2021-001 SA24

1. Unique identification code of the product-type:

### ONDUCLAIR® PLR GO110 177/51 (translucent) - ONDUCLAIR® PLR GO92 177/51 (translucent) - ONDUCLAIR® PLR NERGAL 840 (translucent) - ONDUCLAIR® PLR NERVACLAIR (translucent) - ONDUCLAIR® PLR PO90 76/18 (translucent) - ONDUCLAIR® PLR Corrugated Roll (translucent) - ONDUCLAIR® PLR Flat Roll (translucent) – ONDUCLAIR® PLR PO112 76/18 (translucent) - ONDUCLAIR® PLR H 3 333 39 (translucent)

2. Intended use or uses of the construction product, in accordance with the applicable harmonized technical specification, as foreseen by the manufacturer:

# Light transmitting single skin profiled GRP sheets for discontinuously roof covering for buildings and/or for internal and external wall and ceilings finishes.

3. Name, registered trade name or registered trademark and contact address of the manufacturer as required under Article 11(5):

#### ONDULINE 24 QUAI GALLIENI 92 150 SURESNES – FRANCE www.onduline.com

4. Where applicable, name and contact address of the authorized representative whose mandate covers the tasks specified in Article 12(2): Not Applicable

5. System or systems of assessment and verification of constancy of performance of the construction product as set out in CPR, Annex V:

## System 4

6a. In case of the declaration of performance concerning a construction product covered by a harmonized standard: EN 1013:2012 + A1 2014

7. Declared performances

Characteristics before aging :	Unit	Performance	Harmonized technical specification
External fire performance	-	F <sub>Roof</sub> (NPD)	EN 1013:2012 + A1 2014
Reaction to fire	-	F (NPD)	
Water vapour permeability	mg/(m.h.Pa)	1,5 x 10 <sup>-5</sup>	
Water / air tightness	-	Pass	
Dimensional tolerances	-	Pass	
Mechanical resistance		NPD	
Flexural Tensile/strength	-	NPD	
Resistance to deflection	-	NPD	
Durability (after aging) of :			
<ul> <li>Variation of yellowness index</li> </ul>		NPD	
<ul> <li>Variation of light transmission</li> </ul>		NPD	
<ul> <li>Variation of flexural/tensile strength</li> </ul>		NPD	
Release of dangerous substances	-	NPD	
Resistance to fixings	Principles of fixing are available on the		
	Onduline website		

8. Appropriate Technical Documentation and/or Specific Technical documentation: NO

The performance of the product identified above is in conformity with the set of declared performances. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified in point 3.

Signed for and on behalf of the manufacturer by: Nay TAWILE Managing Director Europe

Herenuw

Suresnes, 27/11/2023 Ver.3