

**DECLARATION OF PERFORMANCE**  
**Under the CPR EU 305/2011**  
**No. 2021-003 SA34**

1. Unique identification code of the product-type:

**ONDUTISS® STRONG PRO**

2. Intended use or uses of the construction product, in accordance with the applicable harmonized technical specification, as foreseen by the manufacturer:

**Bituminous underlays for discontinuous roofing**

3. Name, registered trade name or registered trademark and contact address of the manufacturer as required under Article 11(5):

**Onduline SA**  
**24 Quai Gallieni**  
**92 150 Suresnes – France**  
[www.onduline.com](http://www.onduline.com)

4. Where applicable, name and contact address of the authorized representative whose mandate covers the tasks specified in Article 12(2):

**Not Applicable**

5. System or systems of assessment and verification of constancy of performance of the construction product as set out in CPR, Annex V:

**System 3**

6a. In case of the declaration of performance concerning a construction product covered by a harmonized standard:

**EN 13859-1: 2014**

Notified Body (NB) : **0071 - LNE, Rue Gaston Boissier, 75724 Paris Cedex 15 – For Initial Type Testing**

7. Declared performances

| Characteristics before aging :          | Unit     | Performance | Tolerance | Harmonized technical specification |
|---|----------|-------------|-----------|------------------------------------|
| Reaction on fire                        | Class    | E           | -         | EN13859-1 :2014                    |
| Resistance to water penetration         | Class    | W1          | -         |                                    |
| Tensile strength along MD /CD           | [N/50mm] | 380/300     | ±15%      |                                    |
| Elongation along MD / CD                | [%]      | 30-50/40-60 |           |                                    |
| Tear resistance along MD /CD            | [N]      | 150/150     | ±15%      |                                    |
| Flexibility at low temperature          | [°C]     | ≥-40        | -         |                                    |
| Water vapour resistance                 | [m]      | 50          |           |                                    |
| Dangerous Substances                    | -        | NPD         |           |                                    |
| <b>Resistance to artificial aging :</b> |          |             |           |                                    |
| Tensile strength along MD /CD           | [N/50mm] | 285/195     | ±15%      | EN13859-1 :2014                    |
| Resistance to water penetration         | Class    | W1          | -         |                                    |

8. Appropriate Technical Documentation and/or Specific Technical documentation : **NO**

The performance of the product identified above is in conformity with the set of declared performances. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified in point 3.

Signed for and on behalf of the manufacturer by:

**Christophe ROHART**  
**R&D Director**



Suresnes, 11/06/2021 rev.1