Declaration of Performance

N° DoP: 2023-003 SA47



Unique identification code of the product-type: ONDUTISS® BARRIER REFLEX 150 SD100+

Intended use/es: Flexible sheets of plastic or rubber intended for use as water vapour control layers for buildings

Manufacturer: Onduline

24, quai Gallieni

92150 Suresnes - France

System/s of AVCP: System 3 (reaction to fire)

Harmonised standard : EN 13984:2013

Notified body/ies: 0761, Materialprüfanstalt für das Bauwesen (MPA BS)

0799, Kiwa GmbH Niederlassung TBU

Declared performances:

Essential characteristics	Performance	Harmonised standard
Reaction to fire	E	EN 13984:2013
Watertightness (at 2kPa)	Pass	
Resistance to impact (mm)	NPD	
Resistance to tearing (N)	280/300	
Joint strength (N)	NPD	
Water vapour resistance (m)	≥200	
Tensile strength (longitudinal/transverse direction) (N/50 mm)	440/360	
Elongation at maximum load (longitudinal/transverse direction) (%)	17/17	
Durability - water vapour resistance (after artificial ageing)	Pass	
Durability - Chemical resistance	NPD	
Dangerous substances	NPD	

NPD*: No Performance Declared

The performance of the product identified above is in conformity with the set of declared performances in point 7. This declaration of performance is issued, in accordance with Regulation (EU) N° 305/2011, under the sole responsability of the manufacturer identified above.

Version number : v04

Signed for and on behalf of the manufacturer by:

Nay TAWILE

- Suresnes, le 29/01/2024